

Professional Washer

PW9C

Features and benefits

- **Compass Pro[®] microprocessor offers:**
 - Large display and one control knob for easy program selection
 - Language selection
- PW9C is a large capacity washer suitable for professional users
- Four compartment detergent box for manual dosing of powder or liquid detergent
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- Large door opening for easy loading/unloading
- Drain pump
- Electrical connection: 3 phase or 1 phase
- Water hoses included



Images shown are a representation of the product only and variations may occur.

Options

- Coin meter
- Drain valve

| Main specifications | | PW9C | |
|---|------------------|-----------|-----------|
| Capacity, max. | kg/lb | 9/20 | |
| Extraction | rpm | 1015 | |
| G-factor | | 300 | |
| Heating alternatives | electricity 3 AC | 5.4 kW | |
| | electricity 1 AC | 3.6 kW | |
| | non-heated | x | |
| Consumption data "Colour 60°C" without Pre-wash* | | 5.4 kW | 3.6 kW |
| Total time | min | 50 | 54 |
| Water consumption (cold/hot) | litre | 89/17 | 89/17 |
| Energy consumption (motor/heating) | kWh | 0.25/0.65 | 0.25/0.65 |

* Water temperature 15°C cold water and 65°C hot water

Produced according to ISO 9001 and ISO 14001.

Certified with CB certificate for Low Voltage Directive and S-mark according to the Machinery Directive. Protection class IP X4D.

| Electrical connections | | | | | |
|------------------------|---------------|-------|------------------|----------------|--------------------|
| Heating alternative | Main voltage | | Heating power kW | Total power kW | Recommended fuse A |
| | | Hz | | | |
| Electric heated | 220-240V 1 - | 50/60 | 5.4/7.5 | 5.5/7.6 | 25/35 |
| | 220-240V 1 - | 50/60 | 2.0/3.0 | 2.1/3.1 | 10/16 |
| | 220-240V 3 - | 50/60 | 5.4/7.5 | 5.5/7.6 | 16/20 |
| | 220-240V 3 - | 50/60 | 3.0/4.3 | 3.1/4.5 | 10/16 |
| | 380-415V 3N - | 50/60 | 5.4/7.5 | 5.5/7.6 | 10/16 |
| | 380-415V 3N - | 50/60 | 3.0/4.3 | 3.1/4.5 | 10 |
| | 440V 3 - | 60 | 7.5 | 7.6 | 16 |
| | 480V 3 - | 60 | 7.5 | 7.6 | 10 |
| Steam or Non heated | 220-480V 1 - | 50/60 | - | 1.0 | 10 |

| Water and steam connection | | PW9C |
|---|-----------------------|-----------|
| Water valves | DN | 20 |
| Water pressure | kPa | 150-400 |
| Capacity at 300 kPa | l/min | 16 |
| Drain valve (optional) | ø mm | 50/75 |
| Draining capacity | (pump) l/min | 30 |
| | (drain valve) l/min | 160 |
| Liquid detergent supplies (optional) | | 3 |
| Floor requirements | | |
| Frequency of the dynamic force | Hz | 16.9 |
| Floor load at max extraction | kN | 1.4 ± 0.5 |
| Sound levels | | |
| Sound power/pressure level at extraction* | dB(A) | 75/61 |
| Sound power/pressure level at wash* | dB(A) | 60/46 |
| Heat emission | | |
| % of installed power, max | | 5 |
| Shipping data* | | |
| Weight | net, kg | 135 |
| Shipping volume | m ³ | 0.81 |
| Dimensions in mm | | |
| A | Width | 720 |
| B | Depth | 1130 |
| C | Height | 1113 |
| D1 | | 352 |
| D2 | | 406 |
| E | | 721 |
| F | | 831 |
| G | | 80 |
| H | | 1030 |
| I | | 224 |
| J | | 124 |
| K | | 1010 |
| L | | 910 |
| M | | 278 |
| N | | 98 |
| O | | 239 |
| 1 | Operating panel | 6 |
| 2 | Door opening ø 310 mm | 7 |
| 3 | Detergent box | 8 |
| 4 | Cold water | 9 |
| 5 | Hot water | 10 |
| | | 6 |
| | | 7 |
| | | 8 |
| | | 9 |
| | | 10 |

* A-weighted emission sound pressure level at workingstations.

** Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

