

Salamanders

The fast way
to perfect
results

professional.electrolux.com

Ultrarapid flexibility

Brown, gratin, cook, reheat, keep warm, versatile Electrolux Professional salamanders are fast to heat up and simple to use.



Fast

Just 20 seconds to reach temperature thanks to fast, high efficiency heating system



Easy to use

Super intuitive to use and set time



Efficient

Save on energy and keep your kitchen cooler with automatic contact-controlled heat activation and deactivation



Easy to clean

Extractable trays and grids for stress-free maintenance

Air vents along upper side for better ventilation and reduced heat emission.



Adjustable heating plate with extremely smooth rail system



Touch-controlled plate detecting bar

automatically activates heating elements on contact with dishes so the salamander is only switched on when needed. **Manually start and stop cooking at any time.**



Time is set using highly intuitive control knob and shown on digital display



Range overview

Choose the perfect salamander for you



Ultra Rapid Salamander GN 1/1

- ▶ **PNC 283011**
4 kW 1ph 230V 50/60 Hz
- ▶ **PNC 283012**
4 kW 2N 400V 50/60 Hz
- ▶ WxDxH 600x549x510 mm
- ▶ Drip tray and grill grid included
- ▶ Optional accessory wall hanging bracket (PNC 283035)

Ultra Rapid Salamander
Flawless cooking.
Fast, versatile and efficient.



Open on 3 sides - GN 2/3

- ▶ **PNC 283013**
2 kW 1ph 230V 50/60 Hz
- ▶ WxDxH 400x549x510 mm
- ▶ Drip tray and grill grid included
- ▶ Optional accessory wall hanging bracket (PNC 283035)



Open on 3 sides - GN 1/1

- ▶ **PNC 283014**
4 kW 1ph 230V 50/60 Hz
- ▶ **PNC 283015**
4 kW 2N 400V 50/60 Hz
- ▶ WxDxH 600x549x510 mm
- ▶ Drip tray and grill grid included
- ▶ Optional accessory wall hanging bracket (PNC 283035)



Front open - GN 1/1

- ▶ **PNC 283017**
4 kW 1ph 230V 50/60 Hz
- ▶ **PNC 283016**
4 kW 2N 400V 50/60 Hz
- ▶ WxDxH 759x484x404 mm
- ▶ Drip tray and grill grid included
- ▶ Optional accessory wall hanging bracket (PNC 283036)





Gas salamander - GN 1/1

- ▶ **PNC 283032**
7,4 kW
- ▶ WxDxH 752x421x467 mm
- ▶ Drip tray and grill grid included
- ▶ Optional accessory wall hanging bracket (PNC 283036)

Only the heat you need

Two independent cooking zones, selectable via the clear user interface, offer maximum flexibility with high-efficiency heating elements placed under a glass ceramic panel.





Experience the Excellence
professional.electrolux.com

Follow us on    

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated with the environmental needs of our customers in mind
- ▶ Our technology is ROHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

