

Industrial Ironers

Length Folder IL LF 25, IL LF 30, IL LF 33



Images shown are a representation of the product only and variations may occur.

Features and benefits

- Plug & Play length folding unit at the rear of a C-Flex or IB5700 ironer
- Standard with 1 or 2 primary length folds on one lane. Suitable for single sheets and small flatwork
- Folding programs available on a 5.7" touch screen. Automatically coupled to ironing programs on IB5700
- Automatic speed synchronization with the ironer
- Primary folds by air blast, adjustable in time and air pressure for each program
- Folds items up to 3 m foldable length
- Manual bypass for rejecting torn or stained items
- Machine mounted on wheels

Main options

- Third length fold recommended for foldable dimensions longer than 1800 mm
- Choice of 2,3 or 4 lanes for manually fed items
- Automatic lanes coupling

Electrical connections			IL LF 25	IL LF 30	IL LF 33
Heating Voltage					
EI	230V 1AC 50/60 Hz	kW(A)	0.5 (10)	0.5 (10)	0.5 (10)
Compressed air connections					
Connection diameter		DN	15	15	15
Air consumption		l/min	350	400	450
Air pressure		bar	6	6	6
Sound levels					
Airborne sound level		dB(A)	62	62	62
Shipping data					
Total weight		kg	600	625	680
Total volume		m ³	6,54	7,52	8,12
Shipping dimensions, W x D x H		m	3.3 x 1.1 x 1.8	3.8 x 1.1 x 1.8	4.1 x 1.1 x 1.8
Dimensions in mm					
A Width			3210	3710	4010
B Depth			1610	1610	1610
C Height			1735	1735	1735

