

## Ventilation Equipment Wash-Up Control Panel-4 zones 60x20x40cm

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



641144 (AWS4)

Washing system control panel  
for four zones

### Short Form Specification

Item No. \_\_\_\_\_

External covering panel in pre-varnished metal sheet with IP 55 water protection. Three different washing cycles. Separated electric and hydraulic units for total protection of electronic components. Frontal panel with display and programmable keyboard. Washing cycles can be operated manually or programmed. Cycle time, washing cycle frequency and detergent quantity can be set.

APPROVAL: \_\_\_\_\_

### Main Features

- Possibility to choose three different washing cycles.
- Equipped with alarms signaling lack of detergent and tension.
- Available in various models to guarantee the washing of 1, 2, 3 or 4 zones.
- Pre varnished metal sheet with IP 55 water protection external covering.
- Washing cycle divided in two phases: washing phase uses detergent mixed with hot water while rinsing phase uses only water with the possibility of choosing detergent amount.
- Washing cycles can be programmed daily or weekly with an automatic or manual start set by the operator.
- Complies with main international certification bodies and is CE marked.

### Construction

- Frontal panel equipped with a programmable keyboard containing all the specific functions of washing system and a display showing the current situation of the system.
- Washing system divided in two sections: electric section (to contain electronic card, fuses, block, relay, main switch) and hydraulic section (to contain detergent pump, float, detergent container, detergent strainer, non return valve).

CW11 = Cold Water inlet 1  
EI = Electrical inlet (power)

## Electric

### Supply voltage:

641144 (AWS4) 230 V/1N ph/50/60 Hz

### Total Watts:

0.2 kW

## Key Information:

External dimensions, Width: 600 mm

External dimensions, Height: 400 mm

External dimensions, Depth: 200 mm

Net weight: 15 kg